Unilamp



# STICK





STICK is cylindrical-shaped light column with symmetrical light distribution. The LED light source in combination with a unique 250 degree wide spread lens provides uniform light. It is available with the choices of three different color temperatures from 2700K, 3000K or 4000K in high color consistency and remarkable color rendering index.

**STICK** with HID light source and E27 holder for retrofit lamps are also available. The internal glare suppression louver improves the lighting quality by limiting the upward light emission.

**STICK** is generally installed in the walkways, gardens, parks, commercial areas and open spaces to provide the general lighting from mid-high level. The recommended mounting height is between 3 – 4 meters above the ground.

**STICK Direct** is an evolution of the existing STICK product line. The cylindrical shaped luminaire is available with symmetric or asymmetric light distribution. The efficacy of STICK has been improved to at least 120lm/W and virtually uplight free.

The ambient temperature is rated up to 50°C. STICK direct is available as light column or pole-top light. This makes STICK direct a great choice for new installations and site upgrades.

STICK Direct Light Column















### Specification

- Designed, Manufactured and tested according to IEC 60598.
- LM6 Die Cast Aluminium and Extruded Aluminium body.
- Stainless steel screws.
- Nano Ceramic surface conversion.
- Double layer coating.
- PC protective cover.
- Anodized aluminium louvers.
- Post-cured silicone gasket.
- High quality LED module and driver.
- Installation must be carried out according to the enclosed product manual.

### Available Color

Black Graphite Dark Grey Aluminium Silver White Wooden Brown

(replace the last 2 digits of ordering code with O1) (replace the last 2 digits of ordering code with O2) [replace the last 2 digits of ordering code with O3] [replace the last 2 digits of ordering code with 04] [replace the last 2 digits of ordering code with 06] [replace the last 2 digits of ordering code with 07]








### **STICK**



\* Pole is not includedand has to be ordered separately

# **STICK Direct** POLE LIGHT & POLE TOP LIGHT STICK Direct - Light Column/ 7268 STICK Direct - Pole Top Light/ 7269 Luminaire Performance 3090 - 4770 lm 26 - 36 W 117 - 133 lm/W Beam Options Color Temperature 3000K/ 4000K

On-off/ DIM 1-10V/ DALI/ Casambi



Controller

NEW!

# **STICK**

	Product Code	Product Name	Luminaire Wattage	Beam	ССТ	Luminaire Lumen	Controller
STICK Direct	Ì	STICK Direct – Light Column	26 W	Т1	3000 K 4000 K	3200 - 3210 lm 3360 - 3380 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI
			36 W		3000 K 4000 K	4370 - 4390 lm 4610 - 4630 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI
			26 W	T5	3000 K 4000 K	3090 - 3310 lm 3260 - 3480 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI
	OD-7268		36 W		3000 K 4000 K	4230 - 4520 lm 4460 - 4770 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI
		STICK Direct – Pole Top Light		T1			
			26 W		3000 K 4000 K	3200 - 3210 lm 3360 - 3380 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI
			36 W		3000 K 4000 K	4370 - 4390 lm 4610 - 4630 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI
			26 W	T5	3000 K 4000 K	3090 - 3310 lm 3260 - 3480 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI
	OD-7269		36 W		3000 K 4000 K	4230 - 4520 lm 4460 - 4770 lm	On-Off/ DIM 1-10V/ DALI / CASAMBI

# - Application Reference







# Unilamp Co., Ltd.

461 Ramintra Road, Kannayao, Bangkok 10230 Thailand Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1 Fax : +66[0]2 943 2419

unilamp@unilamp.co.th | online@unilamp.co.th



www.unilamp.co.th